

ECO-HOME with Aluprof

Front entry doors; aren't they one of the most important parts of our home? They protect us from the cold, the rain, and the burglars, to mention just a few examples. Doors also keep us away from street noise. But how do you make the right choice, and buy a door that will meet our expectations and serve us for years?

An issue that requires careful consideration before the purchase is the heat transfer coefficient (U). The lower its value, the more heat will stay with us inside. Aluprof offers panelled doors with the U_D coefficient of 0.50 W/(m²K).

When choosing our door, let's not forget to check out their water resistance. It's the water resistance of the door that will keep the driving rain outside in times of strong winds and heavy rain. The higher the class, the better the door protects our home. Aluprof offers panelled doors rated E1200 (1200 Pa).

Infill panels are included in door leaves based on the MB-79N, MB-86N and MB-104 Passive system, and come in a variety of colours and structures. The elements can be milled, decorated with applications or made of insulated glass. Panelled doors can be fabricated very large and high – up to 1.40 m (W) and almost 2.60 m (H). If, therefore, we dream of an impressive front entrance, this will be the perfect choice. But above all, the door should fit to the style of your home. If our interiors are the traditional ones, we should opt for a leaf with glass panels or wooden-like veneer. Lovers of modern interior can choose among RAL colours, think shade of graphite.

Let's take some time and choose a door with which we will create a beautiful entrance that will enchant our guests and will make us feel like we were in a safe haven.

MB-104 Passive U_D from 0.50 w/m²K

Aluprof's panel door uses thermally insulated aluminium profile system – MB-104 Passive is the most technologically advanced door system offered by Aluprof. The leaf profile can be combined with special infills, aligned with the surface of the frame. The system is dedicated to passive and energy-efficient buildings.

Elegant decorative panels, available in many different patterns and RAL colours and wood effect finishes

Design variants: SI, SI+ and AERO

Central gaskets around the leaf and the frame to seal, cover, and increase the thermal insulation of the door



Technical details:

Frame depth	95 mm
Leaf depth	95 mm
Infill panel thickness	up to 95mm
Maximum dimensions of the leaf	Up to 1.40 m (W), Up to 2.60 m (H)

Technical parameters:

Air permeability	Cs 4, EN 12207
Water tightness	Cs 1200 (1200 Pa), EN 1208
Wind load resistance	Cs 4/B4, EN 1210
Thermal insulation	U_D from 0.50 W/m ² K
Burglary-resistance	RC2


MB-86N

U_D from 0.72 W/m²K

Aluprof's panel doors use thermally insulated aluminium profile system – MB-86N which, just like the MB-104 Passive system, is dedicated to energy-efficient and passive building. The leaf profile can be combined with special infills, aligned with the surface of the frame.

Aesthetically pleasing, decorative panels are available in various designs and colours

They come in four versions: ST, SI, SI + and AERO for a very good thermal performance



Rigid and durable aluminium profiles allow to fabricate of large-dimensioned doors

Weather strips provide high water tightness and air permeability, bringing comfort and money savings

MB-79N

U_D from 0.85 W/m²K

Aluprof's panel door uses popular, thermally insulated aluminium profile system – MB-79N ST, MB-79N SI and MB-79N SI+. The leaf profile can be combined with special infills, aligned with the surface of the frame.



Elegant decorative panels, available in may different patterns and RAL colours and wood effect finishes

Expansion profiles

They come in three versions: MB-79N ST, MB-79N SI and MB-79N SI+, for a very good thermal performance

Technical details:

Frame depth	77 mm
Leaf depth	77 mm
Infill panel thickness	44, 52, 60, 65, 77 mm
Maximum dimensions of the leaf	L up to 1400 mm, H up to 2600 mm


Technical parameters:

Air permeability	Class 4, EN 12207
Water tightness	Class E900 (900 Pa), EN 12208
Wind load resistance	Class C5/B5, EN 12210
Thermal insulation	U _D from 0.72 W/m ² K
Burglary-resistance	RC2

MB-86N PIVOT DOOR – Front entry door with an off-centre rotation axis

 U_D from 0.84 W/m²K

Apart from the basic single-swing version, the front entry door can also be made with an off-centre rotation axis using the MB-86N PIVOT DOOR system.



Technical details:

Frame depth	77 mm
Leaf depth	77 mm
Infill panel thickness	77 mm
Maximum dimensions of the leaf	L up to 1400 mm, H up to 2600 mm
Maximum leaf weight	500 kg

Technical parameters:

Air permeability	Class 4, EN 12207
Water tightness	Class 4A (150 Pa), EN 12208
Wind load resistance	Class C3 (1200 Pa), EN 12210
Operating forces	Class 1, EN 12217
Resistance to torsion	Class 4, EN 1192
Racking	Class 4, EN 1192
Thermal insulation	U_D from 0.84 W/m ² K

BASIC



CLASSIC



EXCLUSIVE



Insert panels




- Triple glazing units U_g 0.5 (W/m²K) or U_g 0.7 (W/m²K)
- Panel thickness from 44 to 72 mm
- U-value for MB-79N SI+ door U_D from 0.98 (W/m²K), for MB-86N SI+ door U_D from 0.8 (W/m²K)
- U-value for MB-86N SI+ door U_D from 0.75 (W/m²K) and for MB-104 Passive door U_D from 0.66 (W/m²K)
- Four construction variants: ST, HI, SI, SI+ & Aero

Aligned on one side






- Triple glazing units U_g 0.5 (W/m²K) or U_g 0.7 (W/m²K)
- Panel thicknesses from 44 to 85 mm
- U-value for MB-79N SI+ door U_D from 0.85 (W/m²K), for MB-86N SI+ door U_D from 0.7 (W/m²K)
- U-value for MB-79N SI+ door U_D from 0.8 (W/m²K), for MB-86N SI+ door U_D from 0.7 (W/m²K) and for MB-104 Passive door U_D from 0.61 (W/m²K)
- Four construction variants: ST, HI, SI, SI+ & Aero

Aligned on both sides

- Triple glazing units U_g 0.5 (W/m²K) or U_g 0.7 (W/m²K)
- 7 mm thick panel (MB-79N), 7 mm (MB-86N) and 95 mm (MB-104 Passive)
- U-value for MB-79N SI+ door U_D from 0.85 (W/m²K), for MB-86N SI+ door U_D from 0.7 (W/m²K) and for MB-104 Passive door U_D from 0.61 (W/m²K)
- Four construction variants: ST, HI, SI, SI+ & Aero



All available models can be inserted into the profiles or glued on one or both sides.

AP21
page 10AP22
page 10AP23
page 11AP24
page 11AP25
page 12AP16
page 16AP18
page 17AP07
page 17AP03
page 17AP08
page 17AP26
page 12AP27
page 13AP28
page 13AP11
page 13AP29
page 14AP13
page 18AP09
page 18AP12
page 19AP15
page 19AP17
page 19AP30
page 14AP19
page 14AP01
page 15AP02
page 15AP31
page 16AP05
page 20AP04
page 20AP20
page 21

The actual product colours may vary from the colours shown



AP21


with a sidelite

- APZ 1600 flush pull handle* Flush inlay
- Alunox 5 mm; on the outside face
- Surface finish: RAL 9005



AP22

- APZ 1600 flush pull handle*
- Glass pane:
outer: VSG 33.1
middle: Satinato
inner: insulating glass with low-E coating
- Surface finish: RAL 7021



AP23

- APZ 1600 flush pull handle*
- 5 mm carves; on the outside face
- AP 3021 kickplate
- Surface finish: DB 703



AP24

with a sidelite

- APZ 1600 flush pull handle*

- AP 3021 kickplate

- AP 3500 anti-scratch protection

- Surface finish RAL 9016

The actual product colours may vary from the colours shown

The actual product colours may vary from the colours shown



AP25

with a sidelite

- AP 200.1400 door pull handle made of high-grade steel/Jatobe wood
- 5 mm flush Alunox inlay; on the outside face
- Glass pane:
outer: VSG 33.1
middle: sandblasted glass, chosen motif
inner: insulating glass with low-E coating
- Surface finish: RAL 9005



AP26

- AP 40.1600 door pull handle made of high-grade steel
- 5 mm flush Alunox inlay; on the outside face
- Glass pane:
outer: VSG 33.1
middle: sandblasted glass, chosen motif
inner: insulating glass with low-E coating
- AP 3400 anti-scratch protection
- Surface finish: RAL 3004



AP27

- AP 60.1600 door pull handle made of high-grade steel
- 5 mm Alunox inlay; on the outside face
- Glass pane:
outer: VSG 33.1
middle: Satinato
inner: insulating glass with low-E coating
- Surface finish: RAL 7016



AP28

- AP 60.1600 door pull handle made of high-grade steel
- 5 mm Alunox inlay; on the outside face
- Glass pane:
outer: VSG 33.1
middle: Satinato
inner: insulating glass with low-E coating
- Surface finish: RAL 9016



AP11

- AP 80.1600 door pull handle made of high-grade steel
- 5 mm Alunox inlay; on the outside face
- Glass pane:
outer: VSG 33.1
middle: sandblasted with transparent frame
inner: insulating glass with low-E coating
- Surface finish: RAL 9016

The actual product colours may vary from the colours shown

The actual product colours may vary from the colours shown



AP29

- AP 46.825 door pull handle made of high-grade steel, finished in black
- U-type carves; on the outside face
- Surface finish: Winchester - ADEC W645



AP30

- AP 130.1030 door pull handle made of high-grade steel
- 5 mm flush Alunox inlay; on the outside face
- Surface finish: RAL 7016



AP19

- AP 60.800 door pull handle made of high-grade steel
- Glass pane:
outer: VSG 33.1
- Glass pane:
middle: sandblasted with transparent strips
- Glass pane:
inner: insulating glass with low-E coating
- Surface finish: RAL 9016



AP01

- AP 40.1600 door pull handle made of high-grade steel
- Flush Alunox inlay; on the outside face
- Glass pane:
outer: VSG 33.1
- Glass pane:
middle: sandblasted with transparent strips
- Glass pane:
inner: insulating glass with low-E coating
- AP 3021 kickplate
- AP 3400 anti-scratch protection
- Surface finish: RAL 9005



AP02

- AP 40.1600 door pull handle made of high-grade steel
- Flush Alunox inlay; on the outside face
- Glass pane:
outer: VSG 33.1
- Glass pane:
middle: sandblasted with transparent strips
- Glass pane:
inner: insulating glass with low-E coating
- AP 3400 anti-scratch protection
- Surface finish: RAL 7016

The actual product colours may vary from the colours shown

The actual product colours may vary from the colours shown



AP31

- AP 46.1625 door pull handle made of high-grade steel
- Carves; on the outside face
- Glass pane:
outer: VSG 33.1
middle: sandblasted with transparent strips
inner: insulating glass with low-E coating
- Surface finish: RAL 7001



AP16

- AP 60.1600 door pull handle made of high-grade steel
- Carves; on the outside face
- Glass pane:
outer: VSG 33.1
middle: sandblasted with transparent strips
inner: insulating glass with low-E coating
- Surface finish: RAL 9016



AP18

- AP 80.1625 door pull handle made of high-grade steel
- Carves; on the outside face
- Flush Alunox inlay; on the outside face
- Glass pane:
outer: VSG 33.1
middle: sandblasted with transparent strips
inner: insulating glass with low-E coating
- Surface finish: RAL 7015



AP07

- AP 60.1600 door pull handle made of high-grade steel
- Flush Alunox inlay; on the outside face
- Carves; on the outside face
- Glass pane:
outer: VSG 33.1
middle: Satinato
inner: insulating glass with low-E coating
- AP 3021 kickplate
- Surface finish: RAL 3004



AP03

- AP 80.825 door pull handle made of high-grade steel
- Glass pane:
outer: VSG 33.1
middle: sandblasted with transparent frame
inner: insulating glass with low-E coating
- AP 3021 kickplate
- Surface finish: RAL 9016

The actual product colours may vary from the colours shown



AP08

- AP 80.825 door pull handle made of high-grade steel
- Glass pane:
outer: VSG 33.1
middle: sandblasted with transparent frame
inner: insulating glass with low-E coating
- AP 3021 kickplate
- Surface finish: RAL 9016

The actual product colours may vary from the colours shown



AP13

- AP 200.1600 door pull handle made of high-grade steel/Jatobé wood
- Flush Alunox inlay; on the outside face
- Glass pane:
outer: VSG 33.1
middle: Satinato
inner: insulating glass with low-E coating
- Surface finish: RAL 7016



AP09

- AP 60.1400 door pull handle made of high-grade steel
- Flush Alunox inlay; on the outside face
- Glass pane:
outer: VSG 33.1
middle: sandblasted glass with transparent frame
inner: insulating glass with low-E coating
- Surface finish: RAL 7016/sweet cherry - ADEC C212



AP12

- AP 50.1200 door pull handle made of high-grade steel
- Glass pane:
outer: VSG 33.1
middle: sandblasted glass with transparent frame
inner: insulating glass with low-E coating
- Surface finish: RAL 9007/RAL 3004



AP15

- AP 50.1200 door pull handle made of high-grade steel
- Carve; on the outside face
- Glass pane:
outer: VSG 33.1
middle: sandblasted with transparent strips
inner: insulating glass with low-E coating
- Surface finish: RAL 9007



AP17

- AP 50.1200 door pull handle made of high-grade steel
- Carve; on the outside face
- Glass pane:
outer: VSG 33.1
middle: sandblasted with transparent strips
inner: insulating glass with low-E coating
- A 330 anti-scratch protection
- Surface finish: DB703

The actual product colours may vary from the colours shown

The actual product colours may vary from the colours shown



AP05

- AP 40.1600 door pull handle made of high-grade steel
- Carved; on the outside face
- AP 3021 kickplate
- Surface finish: RAL 9005



AP04

- AP 60.1600 door pull handle made of high-grade steel
- Flush Alunox inlay; on the outside face
- AP 3021 kickplate
- Surface finish: Vintage - ADEC D825



AP10

- AP 60.1800 door pull handle made of high-grade steel
- AP 3400 anti-scratch protection
- AP 3020 kickplate
- Surface finish: RAL 9006



AP20

- AP 60.1600 door pull handle made of high-grade steel
- Glass pane:
 - outer: VSG 33.1
 - middle: sandblasted chosen motif
 - inner: insulating glass with low-E coating
- AP 3400 anti-scratch protection
- Decorative elements: ornamental frame on the outside
- Surface finish: Vien wallnut - ADEC O102

The actual product colours may vary from the colours shown




Pull handle



AP 40

pull handle, dia. 30 mm
(right-angle holders),
stainless steel,
matte, polished


- AP 40.600 30x600 mm
- AP 40.800 30x800 mm
- AP 40.1000 30x1000 mm
- AP 40.1200 30x1200 mm
- AP 40.1400 30x1400 mm
- AP 40.1600 30x1600 mm
- AP 40.1800 30x1800 mm



AP 60

pull handle, 40 x 10 mm
(right-angle holders),
stainless steel,
matte, polished


- AP 60.600 40x10x600 mm
- AP 60.800 40x10x800 mm
- AP 60.1000 40x10x1000 mm
- AP 60.1200 40x10x1200 mm
- AP 60.1400 40x10x1400 mm
- AP 60.1600 40x10x1600 mm
- AP 60.1800 40x10x1800 mm



AP 100

pull handle, 30 x 30 mm
(right-angle holders),
stainless steel,
matte, polished

- AP 100.600 600 mm
- AP 100.800 800 mm
- AP 100.1000 1000 mm
- AP 100.1200 1200 mm
- AP 100.1400 1400 mm
- AP 100.1600 1600 mm
- AP 100.1800 1800 mm



AP 80

pull handle, 40 x 10 mm
(right-angle holders),
stainless steel, matte, polished
or black finished


- AP 80.625 625 mm
- AP 80.825 825 mm
- AP 80.1025 1025 mm
- AP 80.1225 1225 mm
- AP 80.1425 1425 mm
- AP 80.1625 1625 mm
- AP 80.1825 1825 mm



AP 50

pull handle, dia. 30 mm
(holders bent to the side),
stainless steel, matte, polished

- AP 50.600 30x600 mm
- AP 50.825 825 mm
- AP 50.1025 1025 mm
- AP 50.1225 1225 mm
- AP 50.1425 1425 mm
- AP 50.1625 1625 mm
- AP 50.1825 1825 mm



AP 200

pull handle, dia. 35 - 40 mm
(right-angle holders),
Jatobe/stainless steel,
matte, polished

- AP 200.630 630 mm
- AP 200.830 830 mm
- AP 200.1030 1030 mm
- AP 200.1230 1230 mm
- AP 200.1430 1430 mm
- AP 200.1630 1630 mm



AP 130

pull handle, 30 x 20 mm
(right-angle holders),
stainless steel, matte, polished

- AP 130.630 630 mm
- AP 130.830 830 mm
- AP 130.1030 1030 mm
- AP 130.1230 1230 mm
- AP 130.1430 1430 mm
- AP 130.1630 1630 mm



AP 300

lever handle: 1924216X
stainless steel, natural
anode and inox, white,
anthracite, black

lever handle: 1924218X
stainless steel, natural
anode and inox, white,
anthracite, black



AP 3400

Flush anti-scratch protection,
Alunox



AP 350


Flush anti-scratch protection,
Alunox



AP 30

pull handle, dia. 30 mm
(holders turned 45 deg.),
stainless steel,
matte, polished

- AP 30.600 30x600 mm
- AP 30.800 30x800 mm
- AP 30.1000 30x1000 mm
- AP 30.1200 30x1200 mm
- AP 30.1400 30x1400 mm
- AP 30.1600 30x1600 mm
- AP 30.1800 30x1800 mm



AP 70

pull handle, 40 x 10 mm
(holders turned 45 deg.),
stainless steel,
matte, polished


- AP 70.600 40x10x600 mm
- AP 70.800 40x10x800 mm
- AP 70.1000 40x10x1000 mm
- AP 70.1200 40x10x1200 mm
- AP 70.1400 40x10x1400 mm
- AP 70.1600 40x10x1600 mm
- AP 70.1800 40x10x1800 mm



AP 110

pull handle, 30 x 30 mm
(holders turned 45 deg.),
stainless steel,
matte, polished

- AP 110.600 600 mm
- AP 110.800 800 mm
- AP 110.1000 1000 mm
- AP 110.1200 1200 mm
- AP 110.1400 1400 mm
- AP 110.1600 1600 mm
- AP 110.1800 1800 mm



AP 90

pull handle, 40 x 10 mm
(holders bent forward),
stainless steel, matte,
polished or black finished


- AP 90.600 600 mm
- AP 46.625 625 mm
- AP 46.825 825 mm
- AP 46.1025 1025 mm
- AP 46.1225 1225 mm
- AP 46.1425 1425 mm
- AP 46.1625 1625 mm
- AP 46.1825 1825 mm



AP 46

pull handle, 40 x 25 mm,
semi-circular (right-angle
holders), stainless steel, matte,
polished or black finished


- AP 46.625 625 mm
- AP 46.825 825 mm
- AP 46.1025 1025 mm
- AP 46.1225 1225 mm
- AP 46.1425 1425 mm
- AP 46.1625 1625 mm
- AP 46.1825 1825 mm



AP 210

pull handle, dia. 35 - 40 mm
(holders turned 45 deg.),
Jatobe/stainless steel,
matte, polished


- AP 210.800 800 mm
- AP 210.1200 1200 mm
- AP 210.1600 1600 mm



AP 270


horizontal pull handle

- AP 270 60x550mm



AP 3000

Flush kickplate – Alunox



AP 3201

Flush kickplate – Alunox

Lever handles



AP 130

lever handle, 30 x 20 mm
(right-angle holders),
stainless steel, matte, polished



AP 3400

lever handle: 192411X
stainless steel, natural
anode and inox, white,
anthracite, black



AP 350

lever handle: 192411X
stainless steel, natural
anode and inox, white,
anthracite, black



AP 3201

lever handle: 192411X
stainless steel, natural
anode and inox, white,
anthracite, black



AP 250

horizontal pull handle


- AP 250 480x65mm



130 mm high




60 mm high



30 mm high

ALUPROF 23

Wood-like coatings and RAL colours



// RAL & structural colours*



* All RAL colours and structural colours as per the offer.
The colours may vary slightly from the finished product.

Master-Point
clear glass



Chinchilla
clear glass



Satinato
frosted glass



Master-Ligne
clear glass



Master-Carre
clear glass



Transparent
glass



Master-Point
clear glass



Satinato
frosted glass



Master-Carre
clear glass



Aluprof offers a wide range of glass with motif, glass made of transparent or ornamental glass in its most popular models

All door models come in variants with sidelight and toplight.

Version 1: glass with motif

Version 2: transparent glass

Version 3: ornamental glass

Sidelights and fixed lights include triple glazing units with warm glass spacers. Sidelights (fixed glazing) can be placed either on one or on both sides of the door assembly. Maximum sidelight width: 1400mm.

Triple glazing: U_g from 0.5 to 0.7 W/m²K

For depth of frame from 44-85 mm
(black, warm edge spacer bar)

Quadruple glazing: U_g 0.5 W/m²K

For 95 mm frame depth
(black, warm edge spacer bar)

outer: 6 mm laminated safety glass (VSG)

middle I: sandblasted glass / leaded stained glass / insulating glass with low-E coating

middle II: insulating glass with low-E coating




inner: insulating glass with low-E coating

outer: 6 mm laminated safety glass (VSG)

middle I: sandblasted glass / leaded stained glass / insulating glass with low-E coating

middle II: insulating glass with low-E coating

inner: insulating glass with low-E coating



WWW.HOME.ALUPROF.COM

Please visit our site www.home.aluprof.com to learn more on energy-efficient aluminium systems for the construction industry.



COMFORT IS JUST A STEP AWAY



vrata puerta portière drzwi door vrata puerta portière Tür drzwi door